


SOLO 16 PLUS STUCCHI

13° ULTRA NARROW BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The ultra narrow beam in our 12.60W 1200lm module has a peak intensity of 16929cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

| | |
|--|---|
| CATEGORY IP20 | WATTAGE 12.6W |
| MATERIAL Machined AL 6063-T6 Machined Brass | FORWARD VOLTAGE 48V |
| PAN 360° | SUPPLY TYPE Constant Voltage |
| TILT 90° | DRIVER LOCATION Remote AC to 48VDC |
| LOCKABLE Pan | DIMMING DALI 0-10V 1-10V Casambi |
| WEIGHT 395g 570g* 0.87lb 1.25lb* | |

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES


FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

| | |
|---|--|
| NOMINAL LUMENS 1200lm | BEAM ANGLE 13° |
| DELIVERED LUMENS 1127lm | CRI 92 TYP - 2400K 98 TYP - 2700K/3000K |
| COLOUR TEMPERATURE 2400K 2700K 3000K | TM-30 RF: 95 RG: 101 |
| ACCESSORY HOLDER Separate | WARRANTY 5 Years |
| ACCESSORIES Lenses Louver 55mm (2.16") | LIFETIME L90B10 50,000hrs |
| TM65 17.52kgCO2e | STANDARDS |
| TM66 2.4 | |

Photometry shown is for 3000K module. Please enquire for other CCT photometry.




| MODEL | TRACK & ADAPTER FINISH | LUMINAIRE FINISH | LED CCT | BEAM ANGLE | DIMMING CONTROL |
|-------|--|--|--|--|---|
| 1052C | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 AL - Brushed Aluminium RB - Rubbed Bronze* PB - Polished Brass* SB - Brushed Brass* | <ul style="list-style-type: none"> 2490 - 2400K 90CRI 2798 - 2700K 98CRI 3098 - 3000K 98CRI | <ul style="list-style-type: none"> 13 - Ultra Narrow 13° 15 - Narrow 15° 25 - Medium 25° 40 - Flood 40° 50 - Wide Flood 50° | <ul style="list-style-type: none"> A - 0-10V B - 1-10V C - Casambi D - DALI |

Example Code: 1052C - WH - WH - 309815 - D

*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

15° NARROW BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The narrow beam in our 12.60W 1200lm module has a peak intensity of 14173cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

| | |
|--|---|
| CATEGORY IP20 | WATTAGE 12.6W |
| MATERIAL Machined AL 6063-T6 Machined Brass | FORWARD VOLTAGE 48V |
| PAN 360° | SUPPLY TYPE Constant Voltage |
| TILT 90° | DRIVER LOCATION Remote AC to 48VDC |
| LOCKABLE Pan | DIMMING DALI 0-10V 1-10V Casambi |
| WEIGHT 395g 570g* 0.87lb 1.25lb* | |

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES


FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

| | |
|---|--|
| NOMINAL LUMENS 1200lm | BEAM ANGLE 15° |
| DELIVERED LUMENS 1104lm | CRI 92 TYP - 2400K 98 TYP - 2700K/3000K |
| COLOUR TEMPERATURE 2400K 2700K 3000K | TM-30 RF: 95 RG: 101 |
| ACCESSORY HOLDER Separate | WARRANTY 5 Years |
| ACCESSORIES Lenses Louver 55mm (2.16") | LIFETIME L90B10 50,000hrs |
| TM65 17.52kgCO2e | STANDARDS |
| TM66 2.4 | |

Photometry shown is for 3000K module. Please enquire for other CCT photometry.




| MODEL | TRACK & ADAPTER FINISH | LUMINAIRE FINISH | LED CCT | BEAM ANGLE | DIMMING CONTROL |
|-------|--|--|--|--|---|
| 1052C | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 AL - Brushed Aluminium RB - Rubbed Bronze* PB - Polished Brass* SB - Brushed Brass* | <ul style="list-style-type: none"> 2490 - 2400K 90CRI 2798 - 2700K 98CRI 3098 - 3000K 98CRI | <ul style="list-style-type: none"> 13 - Ultra Narrow 13° 15 - Narrow 15° 25 - Medium 25° 40 - Flood 40° 50 - Wide Flood 50° | <ul style="list-style-type: none"> A - 0-10V B - 1-10V C - Casambi D - DALI |

Example Code: 1052C - WH - WH - 309815 - D

*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

25° MEDIUM BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The medium beam in our 12.60W 1200lm module has a peak intensity of 5149cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

| | |
|--|---|
| CATEGORY IP20 | WATTAGE 12.6W |
| MATERIAL Machined AL 6063-T6 Machined Brass | FORWARD VOLTAGE 48V |
| PAN 360° | SUPPLY TYPE Constant Voltage |
| TILT 90° | DRIVER LOCATION Remote AC to 48VDC |
| LOCKABLE Pan | DIMMING DALI 0-10V 1-10V Casambi |
| WEIGHT 395g 570g* 0.87lb 1.25lb* | |

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES


FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

| | |
|---|--|
| NOMINAL LUMENS 1200lm | BEAM ANGLE 25° |
| DELIVERED LUMENS 1072lm | CRI 92 TYP - 2400K 98 TYP - 2700K/3000K |
| COLOUR TEMPERATURE 2400K 2700K 3000K | TM-30 RF: 95 RG: 101 |
| ACCESSORY HOLDER Separate | WARRANTY 5 Years |
| ACCESSORIES Lenses Louver 55mm (2.16") | LIFETIME L90B10 50,000hrs |
| TM65 17.52kgCO2e | STANDARDS |
| TM66 2.4 | |

Photometry shown is for 3000K module. Please enquire for other CCT photometry.




| MODEL | TRACK & ADAPTER FINISH | LUMINAIRE FINISH | LED CCT | BEAM ANGLE | DIMMING CONTROL |
|-------|--|--|--|--|---|
| 1052C | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 AL - Brushed Aluminium RB - Rubbed Bronze* PB - Polished Brass* SB - Brushed Brass* | <ul style="list-style-type: none"> 2490 - 2400K 90CRI 2798 - 2700K 98CRI 3098 - 3000K 98CRI | <ul style="list-style-type: none"> 13 - Ultra Narrow 13° 15 - Narrow 15° 25 - Medium 25° 40 - Flood 40° 50 - Wide Flood 50° | <ul style="list-style-type: none"> A - 0-10V B - 1-10V C - Casambi D - DALI |

Example Code: 1052C - WH - WH - 309815 - D

*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

40° FLOOD BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The flood beam in our 12.60W 1200lm module has a peak intensity of 2358cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

| | |
|--|---|
| CATEGORY IP20 | WATTAGE 12.6W |
| MATERIAL Machined AL 6063-T6 Machined Brass | FORWARD VOLTAGE 48V |
| PAN 360° | SUPPLY TYPE Constant Voltage |
| TILT 90° | DRIVER LOCATION Remote AC to 48VDC |
| LOCKABLE Pan | DIMMING DALI 0-10V 1-10V Casambi |
| WEIGHT 395g 570g* 0.87lb 1.25lb* | |

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES


FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

| | |
|---|--|
| NOMINAL LUMENS 1200lm | BEAM ANGLE 40° |
| DELIVERED LUMENS 987lm | CRI 92 TYP - 2400K 98 TYP - 2700K/3000K |
| COLOUR TEMPERATURE 2400K 2700K 3000K | TM-30 RF: 95 RG: 101 |
| ACCESSORY HOLDER Separate | WARRANTY 5 Years |
| ACCESSORIES Lenses Louver 55mm (2.16") | LIFETIME L90B10 50,000hrs |
| TM65 17.52kgCO2e | STANDARDS |
| TM66 2.4 | |

Photometry shown is for 3000K module. Please enquire for other CCT photometry.




| MODEL | TRACK & ADAPTER FINISH | LUMINAIRE FINISH | LED CCT | BEAM ANGLE | DIMMING CONTROL |
|-------|--|--|--|--|---|
| 1052C | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 AL - Brushed Aluminium RB - Rubbed Bronze* PB - Polished Brass* SB - Brushed Brass* | <ul style="list-style-type: none"> 2490 - 2400K 90CRI 2798 - 2700K 98CRI 3098 - 3000K 98CRI | <ul style="list-style-type: none"> 13 - Ultra Narrow 13° 15 - Narrow 15° 25 - Medium 25° 40 - Flood 40° 50 - Wide Flood 50° | <ul style="list-style-type: none"> A - 0-10V B - 1-10V C - Casambi D - DALI |

Example Code: 1052C - WH - WH - 309815 - D

*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

50° WIDE FLOOD BEAM



TECHNICAL DESCRIPTION

Solo 16 Plus Stucchi is a Constant Voltage single source LED spotlight that is machined from aerospace grade aluminium 6063-T6 and comes as standard in white, black and brushed aluminium along with three premium brass finishes. It has five site-changeable optics for flexible beam distribution and 360° lockable pan and 90° constant torque tilt. The wide flood beam in our 12.60W 1200lm module has a peak intensity of 1545cd. An accessory holder is available separately that can accommodate 55mm (2.16") lenses and louvers. This product requires an external 48V Constant Voltage LED power supply.

MECHANICAL & ELECTRICAL

| | |
|--|---|
| CATEGORY IP20 | WATTAGE 12.6W |
| MATERIAL Machined AL 6063-T6 Machined Brass | FORWARD VOLTAGE 48V |
| PAN 360° | SUPPLY TYPE Constant Voltage |
| TILT 90° | DRIVER LOCATION Remote AC to 48VDC |
| LOCKABLE Pan | DIMMING DALI 0-10V 1-10V Casambi |
| WEIGHT 395g 570g* 0.87lb 1.25lb* | |

MOUNTING

MOUNTING 48V Stucchi Track Recessed | Trimless Recessed | Surface | Suspended

FINISHES


FINISHES Brushed Aluminium | Black RAL9005 | Traffic White RAL9016 | Rubbed Bronze* | Polished Brass* | Satin Brass*

*Premium & custom finishes are built & finished to order. These are subject to an extended lead time & MOQ.

OPTICAL & STANDARDS

| | |
|---|--|
| NOMINAL LUMENS 1200lm | BEAM ANGLE 50° |
| DELIVERED LUMENS 979lm | CRI 92 TYP - 2400K 98 TYP - 2700K/3000K |
| COLOUR TEMPERATURE 2400K 2700K 3000K | TM-30 RF: 95 RG: 101 |
| ACCESSORY HOLDER Separate | WARRANTY 5 Years |
| ACCESSORIES Lenses Louver 55mm (2.16") | LIFETIME L90B10 50,000hrs |
| TM65 17.52kgCO2e | STANDARDS |
| TM66 2.4 | |

Photometry shown is for 3000K module. Please enquire for other CCT photometry.



| MODEL | TRACK & ADAPTER FINISH | LUMINAIRE FINISH | LED CCT | BEAM ANGLE | DIMMING CONTROL |
|-------|--|--|--|--|---|
| 1052C | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 | <ul style="list-style-type: none"> WH - White 9010 BK - Black 9005 AL - Brushed Aluminium RB - Rubbed Bronze* PB - Polished Brass* SB - Brushed Brass* | <ul style="list-style-type: none"> 2490 - 2400K 90CRI 2798 - 2700K 98CRI 3098 - 3000K 98CRI | <ul style="list-style-type: none"> 13 - Ultra Narrow 13° 15 - Narrow 15° 25 - Medium 25° 40 - Flood 40° 50 - Wide Flood 50° | <ul style="list-style-type: none"> A - 0-10V B - 1-10V C - Casambi D - DALI |

Example Code: 1052C - WH - WH - 309815 - D


*Premium & custom finishes are built to order, subject to an extended lead time & MOQ

SOLO 16 PLUS STUCCHI

DRIVER COMPATIBILITY

MEANWELL | 60W | DIMMING DIRECT TO TRACK

NO. OF LIGHTS PER DRIVER 1 to 4
 MIN DIM LEVEL N/A Dimming direct to track
 VOLTAGE REGION 230V
 FOR NORTH AMERICA No
 WATTAGE 60W
 OUTPUT VOLTAGE 48V
 SUPPLY TYPE Constant Voltage
 DRIVER LOCATION Remote
 MANUFACTURER Meanwell




ORDER CODE PSCV-60-48-N1-MW

LENGTH 162mm (6.38") WIDTH 42mm (1.65") HEIGHT 32mm (1.23")



MEANWELL | 100W | DIMMING DIRECT TO TRACK

NO. OF LIGHTS PER DRIVER 1 to 7
 MIN DIM LEVEL N/A Dimming direct to track
 VOLTAGE REGION 230V
 FOR NORTH AMERICA No
 WATTAGE 100W
 OUTPUT VOLTAGE 48V
 SUPPLY TYPE Constant Voltage
 DRIVER LOCATION Remote
 MANUFACTURER Meanwell




ORDER CODE PSCV-100-48-N1-MW

LENGTH 190mm (7.48") WIDTH 52mm (2.04") HEIGHT 37mm (1.46")



MEANWELL | 100W | DIMMING DIRECT TO TRACK

NO. OF LIGHTS PER DRIVER 1 to 7
 MIN DIM LEVEL N/A Dimming direct to track
 VOLTAGE REGION 120V
 FOR NORTH AMERICA Yes
 WATTAGE 100W
 OUTPUT VOLTAGE 48V
 SUPPLY TYPE Constant Voltage
 DRIVER LOCATION Remote
 MANUFACTURER Meanwell



ORDER CODE USCV-100-48-N1-MW-EN

LENGTH 350mm (13.75") WIDTH 65mm (2.6") HEIGHT 57mm (2.25")

