

Kendo XL wall - Installation Instructions

Please read all instructions prior to installation and keep for future reference!

- | | |
|--|--|
| 1. PRODUCT TO BE INSTALLED BY A QUALIFIED ELECTRICIAN. | 5. WALL MOUNT ONLY |
| 2. USE ONLY WITH CLASS 2 POWER UNIT | 6. SUITABLE FOR INSTALLATION WITHIN THE CLOSET STORAGE SPACE |
| 3. 24 VOLTS DC | 7. TYPE IC |
| 4. SUITABLE FOR DAMP LOCATIONS | 8. INHERENTLY PROTECTED |



7777 Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com

1

junction box
canopy
mounting bracket
fixture wires
fixture

wall

1.1 While holding the fixture, slide the mounting bracket & canopy through the fixture wires.

1.2 Connect the red (24VDC+) & black (24VDC-) power supply wires to the fixture red & black wires.

2

#8-32 screw
canopy
mounting bracket
fixture

wall

Note: Use the provided universal crossbar if canopy does not align to the junction box holes

2.1 Insert the wire nut connections into the junction box. Align the canopy & mounting bracket to the junction box holes and secure using the provided two #8-32 screw.

3

mounting bracket
fixture
lower flange
bracket lip
threaded slot
mounting bracket hole
self tapping screw
lens
film

wall

3.1 Align the fixture lower flange into the mounting bracket lip. Then push the fixture threaded slot to the mounting bracket holes and secure using the provided self tapping screws, refer to diagram above for reference.

3.2 From the bottom of the fixture, remove the protective film from the lens.

END CAPS ARE NOT SHOWN FOR CLARITY