











Latona 3 - Recessed downlight. The Latona 3 is a smaller, stylish square recessed fixture that features the 93+ CRI Accuracy module. This fixture is a small but a powerful option that features stationary positioning to guarantees correct position of light.

Ordering Code

Fixture	512								
	1	2	3	4	5	6	7	8	
Driver		512							
	1	2	3	4	5	6	7	8	

Product Specifications

SAMPLE: Fixture 512 - FL - A90 - 615 - 27 - 07 - 00 - 01 | Driver 910 - 512 - FL - STD - 120 - A90 - 07 - 01

1 - Model	2 - Trim	3 - LED	4 - Refle	ector	5 - CCT	6 - Lum	en	7 - Accessory	
512 · Latona 3	FL · Flanged 99 · Flangeless	A90 • 93+ CRI Accu	*	88° Faceted	27 · 2700K 30 · 3000K 35 · 3500K 40 · 4000K	07 · 700 10 · 100 15 · 150	0 (9.1W)	00 · No Accesso DL · Diffusing Ler	•
8 - Finish	1 - Housing Style	2 - Model	3 - Trim	4 - Driver		Dim Level			Dim Level
01 · White 02 · Black 08 · Silver XX · Custom	 910 · Remote 915 · New construction 920 · IC Housing*1/2/8 	Same as on Fixture	Same as Fixture	LCS · DIM · ELDOLC ·	Non Dimming 0 - 10 Volt Protocol Phase* ³ EldoLED 0 - 10 Volt* ⁴ Dali Protocol* ⁴	N/A 1% 1% 0.1% 0.1%	LUT2W · DMX ·	Hilume Ecodigital* ⁴ 2 Wire for phase* ^{3/4} SENSO* ⁴ Emergency Driver* ^{4/5}	1% 1%
5 - Line Voltage 120 · 120V 277 · 277V 347 · 347V*4/6	6 - LED Same as Fixture	7 - Lumen Same as Fixture	8 - Finish*7 Same as Fixture Only required with Flangeless Trim		Q	Type : —			

^{*1 1000}lm max

^{*2} Not available with flangeless trim

^{*3 120}V only *4 Requires remote housing

^{*5} Specified separately

^{*6} Not available with ELDO, Lutron or DMX

^{*7} Only required with **Flangeless Trim**

^{*8} JA8 Compliant

RECESSED LED DOWNLIGHT



Light Engine

Output: up to 1500lm High Efficacy: up to 80 lumen/Watt

Color Options (CCT): 2500K, 2700K, 3000K, 3500K, 4000K or 6500K

Color Consistency: Range within a 3-MacAdam Ellipse

Color rendering (CRI): 93+ CRI & 50+ R9 Value

Driver

Dimming: 1% dimming standard with 0.1% option

Ripple: Industry leading Low ripple Power Factor > 0.9 Efficiency:

Efficiency over 85%

Class 2 output for safety

Installation: Small Footprint allows retrofit installations


Lumen Option	700lm	1000lm	1500lm
Delivered Lumen	488lm	723lm	1080lm
Fixture Wattage	6.1W	9.1W	14W


Installation

- For new and retrofit installations
- · Easy installation with spring loaded tabs
- · Simple connection between fixture and driver via quick connect
- · Wet rated available

Construction/Finish

- · Powder coated in white, black or silver
- Custom finish are available
- · Cast aluminum
- · Seismic tether
- · Made in Canada













Housing Options

Standard Senso Housing - 910

Dimension









7.0"



Included


Unless specified otherwise, this is provided as standard

Bar hanger


- Included with large 910 box only
- Length: from 14-3/16" to 26"
 - Mounting screws not included
- Driver with enclosure Security wire
- Galvanized steel enclosure
 - Flexible aircraft cable, 12" long Easy to clip snap body included
- * driver can be installed either:


(A) laying on top of ceiling. (B) mounted to the bar hanger and fixed to the ceiling. (C) remote from the fixture, with the bar hanger still used if desired to secure the fixture

New Construction - 915 Flanged




Dimension






New Construction - 915 Flangeless



Dimension



Included

Plaster Frame

Galvanized steel construction with cut-out to

Bar hanger

Length: from 14-3/16" to 26'

Outlet Box


Standard Senso housing 910 included

Security wire

Flexible aircraft cable, 12" long


Easy to clip snap body included


IC Housing - 920





Dimension





Included

IC Housing

- Galvanized steel construction
- Airtight

Includes gasketed junction box

Plaster Frame

Galvanized steel construction

Bar hanger

Length: from 14-3/16" to 26"

Note: Lumen output cannot exceed 1000lm Not available in flangeless



