

LETO 44 Mini T

TRACK LED SPOTLIGHT



Leto 44 Mini T - Track LED Spotlight. LETO 44 Mini T is a track version of the Medium Leto 44 Mini. It offers an articulating, short-stem spotlight combined with a versatile and efficient LED. Excels in display based spaces like galleries, industrial and retail.

Ordering Code

Fixture	664							
	1	2	3	4	5	6	7	8
Driver								
	1	2	3	4				

Product Specifications

SAMPLE: Fixture **664 - A90 - 617 - 27 - 07 - 00 - 01 - 01** | Driver **STD - 120 - A90 - 07**

1 - Model	2 - CRI/LED	3 - Optic	4 - CCT	5 - Lumen	6 - Accessory	7 - Body Color
664 · Leto 44 Mini Single Phase	A90 · Accuracy	617 · 17° 630 · 30° 645 · 45°	25 · 2500K 27 · 2700K 30 · 3000K 35 · 3500K 40 · 4000K 65 · 6500K	07 · 700 (6W) 10 · 1000 (9W) 15 · 1500 (14W)	00 · No Accessory DL · Diffusing Lens HO · Honeycomb	Standard Premium 01 · White 52 · Mocha 02 · Black 53 · Charcoal 08 · Silver 54 · Cerulean 55 · Firebrick XX · RAL
8 - Baffle Color	1 - Driver	Dim Level	2 - Voltage	3 - CRI/LED	4 - Lumen	
Standard Premium 01 · White 52 · Mocha 02 · Black 53 · Charcoal 08 · Silver 54 · Cerulean 55 · Firebrick XX · RAL	STD · Non Dimming LCS · 0 - 10 Volt Protocol DIM · Phase*1	N/A 1% 1%	120 · 120V 277 · 277V	Same as Fixture	Same as Fixture	

*1 120V only

LETO 44 Mini T

TRACK LED SPOTLIGHT



Light Engine

- Output:** up to 1500lm
- High Efficacy:** up to 150 lumen/Watt
- Color Options (CCT):** 2500K, 2700K, 3000K, 3500K, 4000K, 6500K
- Color Consistency:** Range within a 3-MacAdam Ellipse
- Color rendering (CRI):** 90 CRI & 50+ R9 Value

Driver

- Dimming:** 1% dimming standard
- Ripple:** Industry leading Low ripple
- Efficiency:** Power Factor >0.9
Efficiency over 85%
Class 2 output for safety

Installation

- 358° rotation
- 0° to 90° tilt
- Includes track adapter (single or dual phase)

Construction

- Machined aluminum construction
- High quality, scratch resistant powder coated finish in standard, premium or custom colors
- Made in Canada

Accessories

Frosted Lens



Honeycomb



Dimensions

