

LL42-RGB 24V - Installation Instructions

Models LL42-RGB



7777 N. Merrimac Ave
Niles, IL 60714
T 224.333.6033
F 224.757.7557
info@luminii.com
www.luminii.com



Please read complete instruction prior to installation and keep for future reference!

1. Product should be installed by a qualified electrician.
2. Prior to installation ensure power is off at fuse box to prevent electrical shock.

Attention: Always test LL42-RGB before installing. Connect LL42-RGB to power supply to ensure it is working properly and no damage has occurred during shipping.

1

Clean area thoroughly where tape will be installed.

For rough surface installations, it is recommended to apply a layer of Aluminum tape or similar material prior to tape application.

2

NOTE - Avoid bending the LL42-RGB in sharp horizontal angles which may damage the LEDs

Remove the paper backing from the LL42-RGB and firmly press down making sure there are no air bubbles that can cause surface irregularities. **Do not remove the adhesive, removing the adhesive may cause arcing of the Line LED tape.**

3

wire leads
LL42-RGB
solder pads

If required for installation, cut the LL42-RGB strip between two rows of solder pads. Always cut LL42-RGB from end without connector / wire leads.

4

Follow RGB controller and receiver instructions for all wiring connections. Refer to diagram for needed components.

wireless or wired RGB controller

receiver / decoder

24V PSV power supply

LL42-RGB

repeater

LL42-RGB

OPTIONAL